HP N240 23.8-inch Monitor



A modern display with an incredibly thin design, a great complement to forward thinking offices. At a remarkably reachable price point, the HP N240 23.8-inch Monitor is an easy answer to the cutting-edge styles demanded by growing businesses.



3-Sided micro-edge design

Specifically designed with a thin and airy frame, the 3-sided micro-edge allows the display to sit
unobtrusively on top of a desk, or seamlessly sit next to another display for a near borderless
transition between screens.

A reachable price, for the growing business

 A cutting edge design, without razor sharp prices. The HP N240 23.8-inch Monitor was designed with focus to work alongside distinctive businesses who are set apart from the ordinary.

Stunning from all angles

• Wide viewing angles allow for greater position flexibility on your desktop, more accurate around-the-desk review of projects, no matter where you sit.

Featuring

- Rest assured that your IT investment is supported by a three-year standard limited warranty. To extend your
 protection, select optional HP Care Pack Services.¹
- Technicolor Color Certified presets are included in each displays user interface. Certified to bring out colors and details in photos and multimedia like never before.
- Enjoy the benefits of a certified low blue light display directly through the displays menu.
- Reduce power consumption and help lower your costs with an energy-efficient design.

HP N240 23.8-inch Monitor Specifications Table







Panel Active Area 5.2.7 x 29.64 cm Display Size (diagonal) 60.45 cm (23.87) Viewing Angle 178° horizonat; 178° vertical 8 Brightness 250 cdm² 1 Contrast Ratio 1000:1 static; 5000000:1 dynamic 1 Response Ratio 5 ms gray to gray 1 Product colour 80cd/Silver Aspect Ratio 169 Native Resolution 160 (1920 x 1080 @ 60 Hz) Resolutions Supported 101920 x 1080 ms (1680 x 1050; 1500 x 900; 1400 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 O Display Features Anti-glare; in plane switching; LED Baddights; Language selection; On-screen controls; Plug and Play; User programmable 10 ms (1600 ms) 1000 ms (1600		
Display Size (diagonal) 60.45 cm (23.8°) Viewing Angle 178° horizontal: 178° vertical Brightness 250 cdm² 1 1000-1 static; 50000001-1 dynamic 1 Response Ratio 1000-1 static; 50000001-1 dynamic 1 Response Ratio 16-9 Native Resolution FHO (1920 × 1080 @ 60 Hz) Resolutions Supported 1920 × 1080 @ 60 Hz) Resolutions Supported Display Features Anti-glave: in plane switching, LED Baddgints; Language selection, On-screen controls; Plug and Play; User programmable User Controls Brightness: Contrast; Color Control, Image Control, Image Control, Power Control, Menu, Management, Language; Information, Down; Minus (***); Plus (***); My Let HDMI with HDCP support Imput Power Imput Power Imput Power Imput Signal 1564; HDMI with HDCP support Imput Power Imput Signal 1564; HDMI with HDCP support Imput Power Imput Power Imput Signal 1564; HDMI with HDCP support Imput Power Imput Signal 1565; HDMI with HDCP support Imput Power Imput Power Imput Signal 1565; HDMI with HDCP support Imput Power Imput Signal 1566; HDMI with HDCP support Imput Power Impu	Display Type	IPS w/LED backlight
Wewling Angle 178° horizontal; 178° vertical Brightness 250 cd/m²¹ 1000:1 static; 5000000:1 dynamic ¹ 1000:1 static; 5000000:1 dynamic ² 1000:1 static; 5000000000000000000000000000000000000	Panel Active Area	52.7 x 29.64 cm
Rightness 250 cd/m² 1 Contrast Ratio 1000:1 static; 5000000:1 dynamic 1 Response Ratio 5 ms gray to gray 1 Product colour Black/Silver Aspect Ratio 16:9 Resolution FID (1920 x 1080 @ 60 Hz) Resolution Supported 1920 x 1080 @ 60 Hz) Resolutions Supported 1920 x 1080 @ 60 Hz) Resolutions Supported 1920 x 1080 @ 60 Hz) Resolutions Supported 2 Display Features Anti-glarc; in plane switching; LED Backlights; Language selection; On-screen controls; Plug and Play; User programmable User Control; Power Control; Power Control; Plug and Play; User programmable with HDCP support Input Signal 1 VGA; 1 HDM1 with HDCP support Input Signal 1 VGA; 1 HDM1 with HDCP support Input HDCP Input Signal 1 VGA; 1 HDM1 with HDCP support Input Signal 2 VGA; Dever Input Signal 3 VGA; Dever Input Signal 4 VGA; Dever Input Signal 5	Display Size (diagonal)	60.45 cm (23.8")
Contrast Ratio 100:1 static 500000:1 dynamic 1 Response Ratio 5 ms gray to gray 1 Product colour Black/Silver Aspect Ratio 16:9 Native Resolution FH0 (1920 x 1080; 1680 x 1050; 1600 x 900; 1440 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare: In plane switching: LED Backlights; Language selection; On-screen controls; Plug and Play; User programmable User Controls Brightness; Contrast; Color Control: Image Control; Input Control; Power Control; Menu; Management; Language; Information; Down; Minus (*-"); Plus (*+"); Input Signal 1104; 1404; 140Ml with HDCP support Input Voltage: 100 to 240 WC Power Onsumption Dimensions with Stand (W x D x H) S3.9 x 15.2 x 40.2 cm S1.5 x 40.2 cm S2.9 x 15.2 x 40.2 cm Weight 3.4 kg With stand Ergonomic Features Tit: -5 to +22* Physical security Features Security lock-ready (lock is sold separately) Features Features Features Features Certification and Compliance Certification and Compliance Certification Weight With certification Win-10, Win-8, Win-7 Environmental Specifications What's in the box Mointor, External power supply; V6A cable; CD (includes user guide, warranty, drivers); HP Display Assistant	Viewing Angle	178° horizontal; 178° vertical
Response Ratio 5 ms gray to gray 1 Product colour Black/Silver Aspect Ratio 16-9 Native Resolution FID (1920 x 1080 @ 60 Hz) Resolution Supported 1920 x 1080 ; 1680 x 1050; 1600 x 900; 1440 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare; in plane switching; LED Backlights; Language selectors; On-screen controls; Plug and Play; User programmable User Control; Power Control; Input Control; Power Control; Menu, Management; Language, Information; Down; Minus (*-*); Plus (*+*); Ok; Power Input Signal 1 V.G.; 1 HDMI 100 x 90	Brightness	250 cd/m ² 1
Product colour Aspect Ratio 16:9 Native Resolution FHD (1920 x 1080 @ 60 Hz) Product Supported 1920 x 1080; 1680 x 1050; 1600 x 900; 1440 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare; In plane switching; LED Backlights; Language selection; On-screen controls; Plug and Play; User programmable User Controls Brightness; Contrast; Color Control; Image Control; Input Control; Power Control; Menu; Management; Language; Information; Down; Minus (*-1); Plus (*+1); OK; Power Oki; Power Input Voltage; 100 to 240 VAC Power Consumption 15 W (maximum), 14 W (typical), 0.5 W (standby); 20 W (maximum), 18 W (typical), 0.5 W (standby) Dimensions with Stand (W x D x H) Dimensions without Stand (W x D x H) Security lock-ready (lock is sold separately) features Eryonomental Operating temperature; 5 to 35°C Operating humidity, 20 to 80% FRH Energy Efficiency Certification and compliance Certification and Compliance Certification and Compliance Eryonomental Specifications What's in the box Monitor; External power supply; VGA cable; CD (Includes user guide, warranty, drivers); HP Display Assistant	Contrast Ratio	1000:1 static; 5000000:1 dynamic ¹
Aspect Ratio 16:9 Native Resolution FHD (1920 x 1080 @ 60 Hz) Resolutions Supported 1920 x 1080; 1680 x 1050; 1600 x 900; 1440 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare; In plane switching; LED Backlights; Language selection; On-screen controls; Plug and Play; User programmable User Controls Brightness; Contrast; Color Control; Image Control; Input Control; Power Control; Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); Oc. Power Input Signal 1 VGA; 1 HDMI with HDCP support Imput Power Input voltage: 100 to 240 VAC Power Consumption 15 W (maximum), 14 W (typical), 0.5 W (standby); 20 W (maximum), 18 W (typical), 0.5 W (standby) Dimensions with Stand (W x D x H) S3.9 x 3.6 x 32.3 cm Stand (W x D x H) Weight 3.4 kg With stand Ergonomic Features Flit: -5 to +22* Physical security features Environmental Operating temperature: 5 to 35*C Operating temperature: 5 to 30*C Oper	Response Ratio	5 ms gray to gray ¹
Resolution FHD (1920 x 1080 @ 60 Hz) Resolutions Supported 1920 x 1080; 1680 x 1050; 1600 x 900; 1440 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare; In plane switching; LED Backlights; Language selection; On-screen controls; Plug and Play; User programmable User Controls Brightness; Contrast; Color Control; Image Control; Input Control; Power Control; Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Controls (**Power Control); Power Control; Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control (**Power Control); Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control (**Power Control); Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control (**Power Control); Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control (**Power Control); Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control; Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control; Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control; Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control; Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control; Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control; Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control; Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control; Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control; Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control; Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OI; Power Control; Menu; Menu; Minus (*-*); Plus (*+*); OI; Power Control; M	Product colour	Black/Silver
Resolutions Supported 1920 x 1080; 1680 x 1050; 1600 x 900; 1440 x 900; 1280 x 1024; 1280 x 20; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare; In plane switching; LED Backlights; Language selection; On-screen controls; Plug and Play; User programmable User Controls Brightness; Contrast; Color Control; Image Control; Input Control; Power Control; Menu; Management; Language; Information; Down; Minus (*-*); Plus (*+*); OK; Power Input Signal 1 VGA; 1 HDMI with HDCP support Input Voltage: 100 to 240 VAC Power Consumption 15 W (maximum), 14 W (typical), 0.5 W (standby); 20 W (maximum), 18 W (typical), 0.5 W (standby) Dimensions with Stand (W x D x H) Dimensions without Stand (W x D x H) S3.9 x 15.2 x 40.2 cm S3.9 x 3.6 x 32.3 cm Tilt: -5 to +22* Physical security features Filt: -5 to +22* Security lock-ready (lock is sold separately) features Environmental Operating tumperature: 5 to 35°C Operating tumperature: 5 to 35°C Operating tumpidity; 20 to 80% RH Energy Efficiency Compliance Certification and Certification and WEEE; Microsoft WHQ; Certification Win-10, Win-8, Win-7 Environmental Specifications What's in the box Monitor; External power supply; VGA cable; CO (includes user guide, warranty, drivers); HP Display Assistant	Aspect Ratio	16:9
Display Features	Native Resolution	FHD (1920 x 1080 @ 60 Hz)
User Controls Brightness; Contrast; Color Control; Image Control; Imput Control; Power Control; Menu; Management; Language; Information; Down; Minus ("-"); Plus ("+"); OI; Power Input Signal 1 VGA; 1 HDIM with HDCP support Input voltage: 100 to 240 VAC Power Consumption 15 W (maximum), 14 W (typical), 0.5 W (standby); 20 W (maximum), 18 W (typical), 0.5 W (standby) Dimensions with Stand (W x D x H) S3.9 x 15.2 x 40.2 cm Stand (W x D x H) Weight 3.4 kg with stand Ergonomic Features Tilt: -5 to +22* Security lock-ready (lock is sold separately) features Environmental Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance Certification and CE; CB; KC; KCC; NOM; PSB; ICE; TUV-5; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; VCC; FCC; BSM; Vietnam MEPS; Australian-New Zealand MEPS Compliance Environmental Specifications What's in the box Monitor; External power supply; VGA cable; CD (includes user guide, warranty, drivers); HP Display Assistant	Resolutions Supported	1920 x 1080; 1680 x 1050; 1600 x 900; 1440 x 900; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480
Input Signal 1 VGA; 1 HDMI with HDCP support Input Power Input voltage: 100 to 240 VAC Power Consumption 15 W (maximum), 14 W (typical), 0.5 W (standby); 20 W (maximum), 18 W (typical), 0.5 W (standby) Dimensions with Stand (W x D x H) Dimensions without Stand (W x D x H) Sa.9 x 15.2 x 40.2 cm Signal 2 Signal 3	Display Features	Anti-glare; In plane switching; LED Backlights; Language selection; On-screen controls; Plug and Play; User programmable
with HDCP support Input Power Input voltage: 100 to 240 VAC Power Consumption 15 W (maximum), 14 W (typical), 0.5 W (standby); 20 W (maximum), 18 W (typical), 0.5 W (standby) 53.9 x 15.2 x 40.2 cm 53.9 x 3.6 x 32.3 cm Stand (W x D x H) Weight 3.4 kg With stand Ergonomic Features Tilt: -5 to +22° Physical security features Environmental Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance Certification and compliance Certification and compliance Certification Security Arsenic-free display glass; Mercury-free display backlights; Low halogen 2 Environmental Arsenic-free display glass; Mercury-free display backlights; Low halogen 2 Monitor: External power supply; VGA cable; CD (includes user guide, warranty, drivers); HP Display Assistant	User Controls	Brightness; Contrast; Color Control; Image Control; Input Control; Power Control; Menu; Management; Language; Information; Down; Minus ("-"); Plus ("+"); OK; Power
Power Consumption 15 W (maximum), 14 W (typical), 0.5 W (standby); 20 W (maximum), 18 W (typical), 0.5 W (standby) 53.9 x 15.2 x 40.2 cm 53.9 x 3.6 x 32.3 cm 53.9 x 3.6 x 32.3 cm 53.9 x 3.6 x 32.3 cm Weight 3.4 kg With stand With stand Fregonomic Features Tilt: -5 to +22° Physical security features Environmental Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance Certification and compliance Certification and compliance Cester, Kick, KCC, NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; VCCI; FCC; BSMI; Vietnam MEPS; Australian-New Zealand MEPS WEEE; Microsoft WHQL Certification Win-10, Win-8, Win-7 Arsenic-free display glass; Mercury-free display backlights; Low halogen? Monitor; External power supply; VGA cable; CD (includes user guide, warranty, drivers); HP Display Assistant	Input Signal	, , , , , , , , , , , , , , , , , , ,
Dimensions with Stand (W x D x H) Dimensions without Stand (W x D x H) Say x 3.6 x 32.3 cm Stand (W x D x H) Weight 3.4 kg With stand Ergonomic Features Tilt: -5 to +22° Physical security features Environmental Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance Certification and CE; CB; KC; KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; VCCI; FCC; BSMI; Vietnam MEPS; Australian-New Zealand MEPS compliance Certification and CE; CB; KC; KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; VCCI; FCC; BSMI; Vietnam MEPS; Australian-New Zealand MEPS weets; Microsoft WHQL Certification Win-10, Win-8, Win-7 Arsenic-free display glass; Mercury-free display backlights; Low halogen 2 Specifications What's in the box Monitor; External power supply; VGA cable; CD (includes user guide, warranty, drivers); HP Display Assistant	Input Power	Input voltage: 100 to 240 VAC
Dimensions without S3.9 x 3.6 x 32.3 cm	Power Consumption	15 W (maximum), 14 W (typical), 0.5 W (standby); 20 W (maximum), 18 W (typical), 0.5 W (standby)
Stand (W x D x H) Weight 3.4 kg With stand Ergonomic Features Tilt: -5 to +22° Physical security features Security lock-ready (lock is sold separately) Features Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance Certification and Ce; CB; KC; KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; VCCI; FCC; BSMI; Vietnam MEPS; Australian-New Zealand MEPS WEEE; Microsoft WHQL Certification Win-10, Win-8, Win-7 Arsenic-free display glass; Mercury-free display backlights; Low halogen 2 Monitor; External power supply; VGA cable; CD (includes user guide, warranty, drivers); HP Display Assistant	Dimensions with Stand (W x D x H)	53.9 x 15.2 x 40.2 cm
Ergonomic Features Tilt: -5 to +22° Physical security features Security lock-ready (lock is sold separately) features Environmental Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance Certification and compliance Ce; CB; KC; KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; VCCI; FCC; BSMI; Vietnam MEPS; Australian-New Zealand MEPS WEEE; Microsoft WHQL Certification Win-10, Win-8, Win-7 Environmental Arsenic-free display glass; Mercury-free display backlights; Low halogen 2 Specifications What's in the box Monitor; External power supply; VGA cable; CD (includes user guide, warranty, drivers); HP Display Assistant	Dimensions without Stand (W x D x H)	53.9 x 3.6 x 32.3 cm
Physical security features Environmental Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance Certification and compliance CE; CB; KC; KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; VCCI; FCC; BSMI; Vietnam MEPS; Australian-New Zealand MEPS WEEE; Microsoft WHQL Certification Win-10, Win-8, Win-7 Environmental Arsenic-free display glass; Mercury-free display backlights; Low halogen 2 Specifications What's in the box Monitor; External power supply; VGA cable; CD (includes user guide, warranty, drivers); HP Display Assistant	Weight	3
Features Environmental Operating temperature: 5 to 35°C Operating humidity: 20 to 80% RH Energy Efficiency Compliance Certification and CE; CB; KC; KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; VCCI; FCC; BSMI; Vietnam MEPS; Australian-New Zealand MEPS WEEE; Microsoft WHQL Certification Win-10, Win-8, Win-7 Environmental Arsenic-free display glass; Mercury-free display backlights; Low halogen 2 Specifications What's in the box Monitor; External power supply; VGA cable; CD (includes user guide, warranty, drivers); HP Display Assistant	Ergonomic Features	Tilt: -5 to +22°
Operating humidity: 20 to 80% RH Energy Efficiency Compliance Certification and compliance CE; CB; KC; KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; VCCI; FCC; BSMI; Vietnam MEPS; Australian-New Zealand MEPS WEEE; Microsoft WHQL Certification Win-10, Win-8, Win-7 Environmental Specifications What's in the box Monitor; External power supply; VGA cable; CD (includes user guide, warranty, drivers); HP Display Assistant	Physical security features	Security lock-ready (lock is sold separately)
Compliance Certification and compliance CE; CB; KC; KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; VCCI; FCC; BSMI; Vietnam MEPS; Australian-New Zealand MEPS WEEE; Microsoft WHQL Certification Win-10, Win-8, Win-7 Arsenic-free display glass; Mercury-free display backlights; Low halogen ² Specifications What's in the box Monitor; External power supply; VGA cable; CD (includes user guide, warranty, drivers); HP Display Assistant	Environmental	
Compliance WEEE; Microsoft WHQL Certification Win-10, Win-8, Win-7 Environmental Arsenic-free display glass; Mercury-free display backlights; Low halogen 2 Specifications What's in the box Monitor; External power supply; VGA cable; CD (includes user guide, warranty, drivers); HP Display Assistant	Energy Efficiency Compliance	ENERGY STAR® certified
Specifications What's in the box Monitor; External power supply; VGA cable; CD (includes user guide, warranty, drivers); HP Display Assistant	Certification and compliance	CE; CB; KC; KCC; NOM; PSB; ICE; TUV-S; ISO 9241-307; EAC; UL; CSA; ISC; CCC; CEL; CECP; SEPA; VCCI; FCC; BSMI; Vietnam MEPS; Australian-New Zealand MEPS; WEEE; Microsoft WHQL Certification Win-10, Win-8, Win-7
	Environmental Specifications	Arsenic-free display glass; Mercury-free display backlights; Low halogen ²
Warranty Protected by HP, including a 3 year standard limited warranty. Select HP Care Pack Services to extend service contracts beyond the standard warranties.	What's in the box	Monitor; External power supply; VGA cable; CD (includes user guide, warranty, drivers); HP Display Assistant
	Warranty	Protected by HP, including a 3 year standard limited warranty. Select HP Care Pack Services to extend service contracts beyond the standard warranties.

See important legal disclaimers on the last page $% \left\{ \left(1\right) \right\} =\left\{ \left($

Recommended Accessories and Services

HP 5-year Next Business Day Onsite Standard Monitor Hardware Support



Receive 5 years of next business day onsite repair from an HP-qualified technician for your computing device, if the issue cannot be solved remotely. For more information on Care Pack services, please visit www.hp.com/go/cpc. **Product number: U7935E**

Messaging Footnotes

¹ Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit www.hp.com/go/cpc. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

Technical Specifications Footnotes

1 All specifications represent the typical specifications provided by HP's component manufacturers, actual performance may vary either higher or lower.

Sign up for updates

hp.com/go/getupdated

© Copyright 2016 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

ENERGY STAR® and the ENERGY STAR® mark are registered trademarks of the U.S. Environmental Protection Agency. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.

hp

² External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.